

TIMBERPRO

A Komatsu forestry brand

TL755D-WC harvester



Photo may include optional equipment

Operating weight

78,658 lbs. (35,753 kg)

Rated horsepower

350 HP (261 kW) @ 1,920 rpm

Specifications

Engine

Model	Cummins L9	
Type	Water cooled, 4-cycle, XPI fuel system	
Aspiration	eVGT, after cooled	
No. of cylinders	6	
Bore	4.49 in	114 mm
Stroke	5.86 in	145 mm
Engine displacement	543 in ³	8.9 L
Horsepower		
SAE J1995	Rated 350 HP (261 kW) @ 1,920 rpm	
Fan drive type for radiator cooling	Hydraulic, variable speed, auto reverse	
Governor	All-speed control, electronic	
Peak engine torque	1,151 lb-ft (1,561 Nm)	

U.S. EPA Tier 4 Final emission certification

Hydraulic system

Type: load sense, pressure compensated, open loop system and dedicated closed loop systems

Hydraulic control modes	SAE/US/US mod, custom attachment settings	
Pumps	Implement, swing, attachment, dual track, charge, fan, auxiliary	
Main pump type	Variable displacement piston type	
Saw flow	37 gpm	140 L/min
Implement flow	115 gpm	435 L/min

Coolant (refilling) and lubricant capacity

Fuel tank	239 gal	905 L
Coolant	13.5 gal	51 L
Engine	6.25 gal	23.6 L
Hydraulic tank	64 gal	242 L
DEF tank	15 gal	56.8 L

Operating weight

Operating weight	78,658 lbs.	35,753 kg
------------------	-------------	-----------


Swing system

Drive method	Hydrostatic
Swing reduction	Planetary gear
Swing circle, lubrication	External tooth, greased
Holding brake/swing lock	Oil bath multi-disk, spring applied, hydraulic release
Swing speed	6.6 rpm
Swing torque	64,608 lbs.-ft (87.6 kN/m)
Maximum reach to pin	28' 5" (8,661 mm)
Max cutting swath	15' 6" (4,713 mm)
Max tail swing radius	5' 10" (1,778 mm)
Lift capacity @ 20' (6.1 m), @ 4' 11" (1.5 m) above ground	18,000 lbs. (8,181 kg)
Cutting radius - minimum, @ 4' 11" (1.5 m) above ground	12' 11" (3,948 mm)
Bare pin lift at full reach, @ 4' 11" (1.5 m) above ground	10,500 lbs. (4,772 kg)


Frame, drive and axles

Center frame type/design	HD boxed frame structure with flat bottom, storage trunk, integrated fuel tank
Track frame type/design	HD boxed structure, with shoe support
Drive/travel motor type	Hydrostatic
Final drive	Planetary gear
Track link type	Greased, sealed
Track adjuster type	Grease adj, spring tension
Link pitch	8.5" (216 mm)
Number of links (per side)	51
Number of lower track rollers (per side)	11
Track carrier type, how many (each side)	Slider, dual
Travel speed	Two speed ranges
Parking brake method	Oil bath multi-disk holding brake, spring applied, hydraulic release
Steering controls	Pedals
Shoe width (std)	600 mm
Shoe width (max)	700 mm
Maximum drawbar pull	106,739 lbf (48,518 kgf)
Cab leveling front/rear/side, degrees	24/7/24

Dimensions




Transport dimensions: See C, O and P



Dimensions and weights

A	Overall length full reach	37' 5" (11,405 mm)
B	Overall height highest point body	13' 3" (4,039 mm)
C*	Overall transport width	11' 2" (3,400 mm)
D	Track length - overall	17' 5" (5,334 mm)
E	Track length on ground	13' 11" (4,237 mm)
F	Max boom reach	28' 5" (8,661 mm)
G	Track gauge	9' 2" (2,794 mm)
H	Max tail swing radius	5' 10" (1,778 mm)
I	Ground clearance, center frame (std GR)	2' 8" (806 mm)
J	Overall body width, widest point	9' 8" (2,950 mm)
K	Ground clearance, revo frame (std GR)	6' 9" (2,057 mm)
L	Boom reach @ 4' 11" (1.5 m) above ground	9' (8,534 mm)
N	Machine height, rear of engine hood	12' (3,658 mm)
O	Overall height for transport (std)	12' 6" (3,810 mm)
P	Length on ground for transport	35' 9" (10,897 mm)
	Ground pressure	9.34 psi (0.66 kg/cm ²)

*With 600 mm tracks



Range of motion chart TL755D-WC harvester

A	37' 4" (11,371 mm)
B	28' 5" (8,668 mm) @ 4' 11" (1.5 m) above ground

Equipment

Engine and related components

350 HP (261 kW) Cummins QSL9 (Stage V)	●
1,151 lb-ft (1,561 Nm) @ 1,920 rpm	
Single module DOC/DPF/SCR	●
eVGT, after cooled	●
Hydraulic variable speed cooling fan with auto reverse	●
Air cleaner, dual element with dust collector	●

Operator environment

ROPS/FOPS/OPS certified cabin with three egress routes	●
Reinforced roof hatch, removal tool	●
Skylight	●
1.25" (32 mm) front window	●
Digital climate control system, filtered fresh air intake and pressurized cabin	●
AM/FM/WB radio with Bluetooth® and USB input	●
IQAN MD4 HD control system with 10" touchscreen	●
Left and right joystick electrohydraulic proportional controls for machine operation	●
Coordinated boom operations	●
4-way leveling	●
Automatic leveling control	○
Variable speed travel control	●
Standard seat – air ride and heated, high back with lumbar adjust, folding armrests	●
Deluxe seat – air ride, heated and cooled, high back with lumbar adjust, folding armrests	○
4 pt seat belt harness	●
Rear mounted camera system with dedicated monitor	●
Travel alarm	●
Auxiliary power port connector, 12V	●
Interior LED lights	●
Fire extinguisher	●
English decals	●
Paint - TimberPro red	●
Paint - custom color	○

Serviceability

Rearward open engine hood, power raise	●
Perforated panel, heavy duty service doors and side-hinged cooler doors with tool-less latch closures	●
Retractable step for operators cabin	●
Hydraulic tank electric vacuum system	●
Electric hydraulic oil fill transfer pump	●
Storage trunk, ground level access	●

Electrical system

24V electrical system with battery disconnect	●
Alternator, 100 ampere, 24V	●
Batteries, 2×12V	●
Battery disconnect switch	●
Working lights - LED high intensity lighting	●
LED lighting on work equipment, guarded	●

Standard equipment ●

Optional equipment ○

TimberPro Inc reserves the right to change specifications without notice or obligation. Product illustrations may be equipped with optional equipment.

Hydraulic system

Implement pump	●
Combination hydraulics, valves and plumbing for harvester configuration	○
Charge filter non-bypass, 6 micron	●
Return filters with bypass, 10 micron	●
Case drain filter with bypass, 10 micron	●
Hydraulic air-to-oil cooler	●
Harvester hydraulics, fixed arm controlled fall, tool tilt	○
Harvester hydraulics, fixed droop arm	○
Harvester hydraulics, telescopic arm	○
Hydraulics for other attachments	○

Guards and covers

Work equipment cylinder guards, deflector	○
Sliding protective cover, boom to chimney	○
Carbody debris shields, rubber	●
Boom lines debris shields, rubber	○
Track rail rock guards, full length	●
Engine air intake deflector	●

Frame, undercarriage and tracks

TL carbody, leveling	●
Wide width boxed frame flat bottom forestry carbody with storage trunk and fuel tank	●
Wide width carbody with integrated tethering points	●
Heavy duty towing attachment point	●
24" (600 mm) single grouser track shoes	●
28" (700 mm) single grouser track shoes	○
Track carrier sliders, dual	●
Track rollers, heavy duty, 11 per side	●
51 links per side, sealed	●
Heavy duty spring track tensioner	●
Parking/travel brake, wet multi-disk, hydraulic release	●

Upper swing system, work equipment and attachments

Continuous rotation upper, dual-ball, lubricated swing mechanism	●
Planetary gear swing reduction drives, with wet multi-disk swing holding brake	●
Hydraulic swing energy recovery system	●
Harvester boom and arm work equipment, fixed, droop arm	○
Harvester boom and arm work equipment, telescopic arm	○
Processor (forwarder boom) and arm, telescopic arm	○

Optional equipment

Komtrax monitoring system	○
Fire suppression system	○
Diesel Espar pre-heater with timer	○
120V AC plug-in engine block pre-heaters and plug-in hydraulic tank heater	○
Uptime kit	○

Product designs, specifications and/or data in this document are provided for informational purposes only and are not warranties of any kind. Product designs and/or specifications may be changed at any time without notice. The only warranties that apply to sales of products and services are Komatsu's standard written warranties, which will be furnished upon request.

Komatsu and other trademarks and service marks used herein are the property of Komatsu Ltd., Komatsu America Corp., Komatsu Mining Corp. Komatsu Germany, or one of their affiliates, or the respective owners or licensees.

KOMATSU

komatsu.com

