

Model 1000 Mine Air Systems Technical Data

Performance benefits

- Rugged design specifically engineered for surface mining applications
- Modular design for unmatched changeout speed and convenience
- Unique weather-sealed roofplate eliminates dust and water leaks into the cab and electrical room
- Stainless steel construction
- Designed for maintenance ease
- Designed specifically for ozone friendly R134A refrigerant
- High efficiency air filters to suit each application
- Industrial-sized super efficient filter-pressurizer with air pre-cleaner
- Smooth and quiet scroll technology compressor

Komatsu Mine Air Systems (MAS) climate control units provide air conditioning, heating, filtration and pressurization comforts to the operator's cab. Advanced MAS climate control technology sustains ultimate operator comfort and efficiency by automatically maintaining an even floor-to-roof temperature and a regulated, filtered air flow.

The MAS model 1000 will control climate condition of operator cabs and electrical rooms on electric mining shovels, drills and draglines – and is manufactured and distributed worldwide by Komatsu.

Through modular design, an entire unit can be changed out in just 60 minutes. Individual electrical and control modules can be replaced in as little as ten minutes with no special tools. Maintenance is also simplified.



For more information, contact
a local Komatsu Mining
representative or visit
komatsu.com

Applications

The MAS model 1000 unit is a complete operating system requiring only a power supply to function. Ideal applications include shovels, drills and draglines. The unit can be deck or roof mounted.

Additional considerations:


- Installation expertise required:
 - Electrician
 - Welder
 - Mechanic
 - Air conditioning experience
- Power requirement 30 amp:
 - 480/3/60 AC or
 - 380/3/50 AC (see specs.)

The following are components/options available on the MAS model 1000 unit:

- Filter – pressurizer with air pre-cleaner
- Silica dust and diesel emission packages
- Cooling only option

Components/options


Model 1000 installation (roof mount application shown)



Technical Characteristics

Feature	Specification	Feature	Specification
Description	Roof or beside-the-cab mounted climate control system with optional remote mounted dedicated fresh air pressurizer	Exchangability (modularity)	Complete system – 60 minutes Electrical module – 20 minutes Control module – 10 minutes
Electrical	460 VAC, 3 Phase, 60 Cycle 380 VAC, 3 Phase, 50 Cycle	Switch gear	High quality contactors and thermal overloads all circuits Safety contactor, fuses, auto-reset, and main reset limits-heaters Fused disconnects main, heater, control circuits
Recirculated airflow	High speed - 1000 cfm Low speed - 650 cfm 1 x 250 mm EC blower	Cooling capacity	30,000 Btu/hr @ 75°F DB/65°F WB
Safety controls	Field replaceable without refrigerant loss Digitally monitored low and high pressure	Capacity control	Low load idle (hot gas bypass) valve Externally equalized thermostatic expansion valve
Compressor ROHS	Compliant scroll, hermetically sealed	Compressor oil	Polyolester (POE)
Refrigerant	R-134A	Heating capacity	11.4kW at 480 VAC/380 VAC Fully proportional control from 0 to 100% of capacity (stageless)
Pressurization	170 cfm @ 60 Cycle with clean filter, 20% reduction at change interval Self-cleaning pre-cleaner Maintainable second stage filter cup Donaldson radial seal disposable filter element (no fasteners). Cast aluminum, high speed impeller, operating range 178 mm (7") w.c.	Control	Standard Electric Controller (SEC – analog control) Mine Logic Controller (MLC) digital control
Filters	Disposable 65% efficient in-cab filter in standard plenum configurations Custom filter plenums from 65% (Hepa 99% @ .1 micron*) to suit individual requirements *By special order only	Construction	Cases 16 gauge 316 stainless steel, polished finish Coils copper tube/copper fin-8 fins/in
Physical size	41" long, 30" wide, 33.5" high (1041 mm x 762 mm x 851 mm)	Weight	327 kg (720 lbs)

Model 1000 dimensions



Product designs, specifications and/or data in this document are provided for informational purposes only and are not warranties of any kind. Product designs and/or specifications may be changed at any time without notice. The only warranties that apply to sales of products and services are Komatsu's standard written warranties, which will be furnished upon request.

Komatsu and other trademarks and service marks used herein are the property of Komatsu Ltd., Komatsu America Corp., Komatsu Mining Corp., or one of their affiliates, or the respective owners or licensees.



komatsu.com

